



Optimo Anamorphic 30-72 A2S

Wide Compact Anamorphic Zoom



Specifications

Zoom ratio	2.4x
Focal Length	30 - 72 mm
Aperture	f/3.6 – T4
Close Focus	2 ft 2 in – 0.65 m
Internal Focus	Yes
Image coverage	4 perf. scop +: 28.8 mm diagonal
Weight (approx.)	5.3 lbs – 2.4 kg
Length	227 mm
Front diameter	114 mm

MAIN FEATURES

- 2:1 horizontal squeeze achieved by multiple glass elements behind lens iris
- Perfect homogeneity of color, contrast, resolution and low distortion typical of the Optimo series
- Constant T4 across zoom range
- Minimal breathing suitable for rack focusing
- Close focus of 2 ft 2 in - 0.65 m combined with the extremely wide field of view facilitates production in tight location/sets
- Very low distortion on all focal lengths and at all focus distances
- Great flare and ghost image suppression
- The lightest and most compact anamorphic zoom in the market: 5.3 lbs - 2.4 kg and 227mm long
- Precise and ergonomic focus ring with scale rotation of 320 degrees and over 50 focus witness marks
- Interchangeable focus scale ring from feet to meters
- Front diameter of 114 mm retains compatibility with accessories used with Compact Optimo lenses (matte boxes, filters)
- Adapted to extreme production environments (passive athermalisation from -20°C to +40°C)
- PL mount lens. Easily interchangeable to PV or Canon EF mounts
- Compatible with ASU servo unit (integrated motors for FTZ remote control through industry standard control systems)

Available accessories



PV/EF Mounts



ASU

Field of view for 35 mm 4 perf. (21.95x18.6 mm, 27mm diagonal)

Focal Length	30 mm	72 mm
Horizontal angular field of view	72.5°	34°
Vertical angular field of view	34.4°	14.7°