



# Optimo Style 48-130

Lightweight  
Mid-Range Tele Zoom



## Specifications

Zoom ratio	2.7x
Focal length	48-130 mm
Aperture	T3 with no ramping
Close Focus	3 ft 1" - 0.94 m
Internal Focus	Yes
Image coverage	Up to 34.6 mm
Weight (approx)	4.3lb - 1.95kg
Length	206 mm
Front diameter	114 mm

## MAIN FEATURES

- 2.7x zoom range with a telephoto position of 130mm in an extremely compact form factor
- Constant aperture T3 throughout the entire zoom range
- Enhanced image circle to Ultra S35 up to 34.6mm. Fully covers RED 8K Helium sensor
- Compact and very light (1.95kg / 4.3lb). Ideal for handheld, Steadicam, compact gimbals and drones
- Superb image quality with minimal aberration
- Color reproduction matches the highly acclaimed OPTIMO lens series
- Extremely well controlled distortion
- Internal focus, minimal breathing
- Precise and ergonomic focus ring with scale rotation of 320 degrees with over 20 precise focus witness marks
- Compatible Angenieux Servo Unit (integrated motors for FTZ remote control through industry standard control systems)
- Compatible with Optimo 1.4x and 2x extenders (67-182mm at T4.2 with 1.4x, 96-260mm at T6 with 2x)
- Precise and rugged travelling of the zoom and focus groups using Angenieux classic rod mechanical guiding system
- Suited for extreme production environment (temperature range from -20°C to +45°C)
- Available in PL mount. Easily interchangeable to Panavision PV, Canon EF mounts

## Available accessories



PV/EF Mounts



Extender or  
Format Adapters  
1.4x & 2x



ASU

## Field of view for 22x16 mm

Focal Length	48 mm	130 mm
Horizontal angular field of view	25.6°	9.8°
Object dimensions at MOD (mm)	386x281	144x105